

# ELEVATOR

EL-15 / -25 / -29 / -35 / -50

EL1.13.1907.GB



*EL with optional motor and V-belt drive*

*The EL elevator is suited for transportation of a wide range of products; also suitable for oleaginous seeds*

The elevator is constructed of head and boot sections with a number of leg sections according to the height of the elevator.

The EL elevator offers the below features:

- Lower leg section with access for belt mounting.
- Head section with bracket and free shaft for mounting of motor.
- Boot section with adjustment device for belt tensioning.
- Clean-out door.
- Oil resistant belt.

- Buckets made of steel.
- Distance discs between buckets and belt.
- Inspection window in lower leg section.
- Elevator feet.

The elevator is of steel construction.

#### Options:

- *Belt speed monitor, PLC operated*
- *Belt alignment monitor*
- *Mechanical belt brake*
- *Air cleaning device in boot section*
- *Manually operated slide gate in boot section for clean-out*
- *Inlet hopper and safety grid for this*
- *Explosion relief door*
- *Plastic buckets*

## EQUIPPED FOR CHANGE

We provide valuable insights, so you can make qualified decisions

## ELEVATOR

EL-15 / -25 / -29 / -35 / -50

### TECHNICAL SPECIFICATIONS:

	EL-15	EL-25	EL-29	EL-35	EL-50
Belt width mm	100	140	250	250	350
Height, max. m	15	20	30	30	45
Belt speed m/sec.	2	2	0.75	2	2

### DISTINGUISHING ADVANTAGES:

- Totally enclosed design offering maximum security during operation
- Highly flexible construction to meet a wide range of requirements (height, belt width, belt speed, and belt quality) and to suit individual plant layouts
- Choice of different elevator buckets to give the best possible transportation of a wide range of products ensuring correct filling and emptying of the product
- Easy clean-down when changing from one product to another
- Low maintenance costs