

SCREEN CLEANER

PC-600 / -1000 / -1250 / -1500

PC1.11.1805.GB



Photo shows machine with covered sieveboat [option]

The PC screen cleaner is designed for pre- or fine cleaning, grading, and calibration of a large variety of products

For capacity and all other specific information see the back page.

The PC pre-cleaner offers the below features:

- Inlet with weight loaded valve (PC-600 & PC-1000); inlet with feed roll with counter weight (PC-1250 & PC-1500).
- Screen section consisting of one sieveboat with 1 scalping screen layer and 1 sand screen layer; both with manually adjustable inclination of 4°, 6°, 8°, or 11°.

- In total 4 screen segments with standard perforations above 2 mm; all screen segments with rubber ball cleaning.
- Fixed drive and motor.

The machine is of steel construction with sieveboat of laminated wood.

Options:

- *Covering of sieveboat with aspiration spout*
- *Inlet with feed roll with counter weight for PC-600 and PC-1000*
- *Aspiration system for prime product*

EQUIPPED FOR CHANGE

We provide valuable insights, so you can make qualified decisions

SCREEN CLEANER

PC-600 / -1000 / -1250 / -1500

TECHNICAL SPECIFICATIONS:

	PC-600	PC-1000	PC-1250	PC-1500
Screen size L=800 mm x W	600	1000	1250	1500
Screen area m ²	1.92	3.2	4	4.8
Pre-cleaning capacity t/h	12	20	24	30
Fine cleaning capacity t/h	1.2	2	2.4	2.8

Pre-cleaning capacity: estimate [guideline] based on wheat with max. moisture content of 18%.

Fine cleaning capacity: estimate [guideline] based on pre-clean wheat with max. moisture content of 14%.

DISTINGUISHING ADVANTAGES:

- Easy to install
- Simple manual adjustment of screen inclination
- Easy clean-down when changing from one product to another
- Low maintenance costs

